



064-023-2639  
Environmentally Preferred Flooring



# CLICK PRO<sup>®</sup>

Floors For Great Interior



## High Performance Resilient Flooring



phthalate free



formaldehyde free



easy maintenance



waterproof surface



abrasion resistant



underfoot comfort



slip resistant



sound absorption



indentation residual



stain resistant



fire reaction



residential & commercial use



termite retardant



antimicrobial surface

Made from 100% virgin PVC and EU approved non - phthalate plasticizer (DOTP)



SK 3808 W Ivory Oak



SK 3813 W Grey Oak



SK 3856 W American Chestnut

Wearlayer : 0.5mm with antimicrobial protective coating



SK 3822 W Akassika Spruce



SK 3811 E Artisan Parquet



SK 3835 W European Oak

Note : Samples for colour illustration only.  
Will not reflect full design and tonality.



SK 3855 E Sunny Oak



SK 3868 W Albizia



SK 3877 W Honduras Rosewood

Tile 12" x 24" x 5mm  
Size : 305 x 610 x 5mm



SK 3658 T Mount Everest



SK 3699 T Buio Pietra



SK 3660 T Klasse Formigon



# CLICKPRO®

Floors For Great Interior

## The Benefits

CLICKPRO planks and tiles are high performance floating floor made from high quality vinyl. The aesthetics of hard wood and natural stone are now combined with the resistance of pure vinyl to scratches, scuffing, stain and dirt. CLICKPRO surface is impervious to water and can be deployed in places that receive spills. With its slip resistance surface and underfoot resilience, you can enjoy walking on it barefoot. Being glueless, it is also eco friendly to install and contributes to improved indoor air quality. The aesthetics are unsurpassed with the natural wood emboss and non-repeat wood pattern at the two ends of each plank and tile. The surface is treated with antimicrobial protective coating. CLICKPRO LVT click offers superior impact sound insulation as compared to other click system such as SPC and laminated floors. With easy maintenance, CLICKPRO are floors for great interior.

## Application

CLICKPRO can be installed in the residential and general commercial environment. In residential, it can be fitted in the bedroom, study, living and dining area. It can also be installed in dry kitchen and entrance of bathroom by sealing the perimeter edges with silicon caulk. It can be readily installed over existing hard surfaces and in moisture prone area where wood flooring and glue-down products are off limit. For commercial use, with its 0.5mm high performance wear layer, CLICKPRO is well suited for use in offices, care centres, retail outlets and institutions.

## Installation & Care

**Before install check list** \*Substrate must be structurally stable, flat and smooth. \*Check floor level variation is <3.0mm across any 1.2 metre. \*Check subfloor moisture level must be <90% RH. \*Floor to be acclimatized on site 12 hours at room temperature before installing. \*Height variation between ceramic tiles, plywood and any other existing flooring must be patched and levelled before laying over with new click flooring. \*For areas with rolling load and high foot traffic, thicker product thickness should be used. \*All carton boxes, planks and tiles must be stored completely flat on hard surface.

**During install check list** \*For every 5 metres room length, leave a 2mm wall gap. \*Leave an expansion gap every 10 metres. \*All joints must be properly adjoined. \*For wet area use, fill the perimeter gaps with a high quality silicone caulking.

**Notes to end user** \*Do not spread excess water such that they seep into wall gaps. \*Avoid exposure to long period of peak hours direct sunlight without protection of shades. \*Do not drag heavy furniture across the surface. \*For the use of chair with castor wheel, a protective surface pad is recommended.

**Maintenance** \*Floors should be swept or vacuum regularly to remove loose dirt. \*Damp mop as needed using clean water and a PH neutral floor cleaner. Cleaner should be free of ammonia and hydrochloric acid. \*Aging floor can be restored by machine buffing and polishing.

## Product Specifications

CLASSIFICATION	STANDARDS		CLICKPRO®
Size	ISO 24342	mm	Plank : 229 x 1219 mm   Tile : 305 x 610 mm
Thickness *	ISO 24346	mm	5.0 mm ( Micro-Bevelled Edge )
Wear layer *	ISO 24340	mm	0.50 mm
Curling *	ISO 23999	mm	≤2 mm
Packing	-	Carton	8 planks / box (2.23 m <sup>2</sup> )   9 tiles / box (1.67 m <sup>2</sup> )
Dimensional stability *	ISO 23999	%	≤2
Residual Indentation *	ISO 24343 -1	mm	≤0.1mm
Effect of castor chair *	ISO 4918	-	No visible damage
Abrasion resistance *	EN 660 - 2	mm <sup>3</sup>	Weargroup : T
Stain resistance *	ISO 26987	Index	Complied
Classification ( level of use )	EN 429	Class	Heavy domestic (class 23 ) General commercial (class 32 )
Impact sound insulation	ISO 717 - 2	dB	6
Colour fastness *	ISO 105 - B02	Degree	>6
Fire classification *	EN 13501-1	Class	Bfl-S1 ( flame spread / smoke )
Electrical propensity	EN 1815	kV	< 2
Cigarette burn resistance *	EN 1399	Class	Class 3
Formaldehyde emission	EN 717 - 1	mg/m <sup>2</sup>	Not detected
Pentachlorophenol	EN 14041	mg/kg	Not detected
Heavy metal	EN 71 Part 3	mg/kg	Not detected
Slip resistance *	SS 485 ( Dry friction )	COF	≥0.4
	SS 485 ( Wet friction )	CI	Class X (35 to 44)
Phthalate	EN 14372 : 2004	mg/kg	Not detected
Antimicrobial activities	ISO 22196	Bacteria	>99% reduction ( ATCC 6538P / 8739 )
	ISO 846	Fungi	No growth observed ( ATCC 6205 / 6275 / AS3.2942 / 3875 / 3984 )

\* Complies with Singapore HDB Material Listing performance criteria, other test standards are additional. CLICKPRO offers a 10 years residential wear durability and 3 years commercial limited warranty against manufacturing defects. By following the installation and care, CLICKPRO will provide a beautiful and lasting floor for many years to come.